



AGRIMAX RT 765



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version STANDARD

Tire Type TL

Tyre size 620/70R38

LI/SS 170;D

Dimensions US Standard

USA Code	94063482
SW (in)	24.6
OD (in)	72.2
SLR (in)	32.6
RC (in)	220.1
Rim Rec	DW 20 B
Rim Alt	DW 18 L; W 18 L
ECE	E11-106R-005997
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35	41	47
40	5160	6080	7010	7800	8730	9520	10450	11240	12300	13230
30	5420	6390	7360	8200	9170	10010	10980	11810	12920	13890
25	5650	6670	7680	8550	9570	10440	11450	12310	13480	14480
20	5940	7000	8070	8980	10040	10960	12030	12930	14150	15210
5 LT	6920	8160	9400	10460	11710	12760	14010	15070	16490	17720
5 HT	5940	7000	8070	8980	10040	10960	12030	12930	14150	15210

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..