



MULTIMAX MP 529



MULTIMAX MP 529 is a steel belted multi-purpose radial tire designed for telehandlers in industrial applications. Its tread design has been specially developed for hard surfaces. The strong sidewall and the larger footprint area ensure outstanding stability in lift mode. MULTIMAX MP 529 also features a strong puncture-resistant casing and is made of a special cut-and-chip-resistant compound providing extraordinary durability and a long service life.

US Standard

 Radial

Промышленность ▪ Телескопический погрузчик

Version

STEEL BELTED

Tire Type

TL

340/80R18

143;A8/B

undefined US Standard

USA Code	94054305
SW (in)	13.5
OD (in)	39.4
SLR (in)	17.5
RC (in)	118.4
Rim Rec	11; 11 SDC; W 11
Rim Alt	W 10; 12; 12 SDC
ECE	E11-106R-002972

Load Capacity (US)

mph / psi	23	29	35	41	46	51	58	61	64
30	2890	3430	3910	4450	4990	5360	6010	-	-
25	2890	3430	3910	4450	4990	5360	6010	-	-
20	3100	3670	4190	4770	5350	5730	6440	-	-
15	3210	3800	4340	4940	5540	5940	6670	-	-
5 Cyc.	3530	4330	5100	5860	6680	7260	8210	8660	9020
Static	5400	6640	7810	8990	10230	11130	12590	13270	13820

24-03-2026