



US standard



GROWING TOGETHER

# TF 9090



PRODUCT DATA SHEET



Bias



Performance



Steering Control



# TF 9090

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 12"	94033898	4.00 - 12	3.00 D	2.50 C	4.4	20.9	10.0	61.9	14	9	STD	4	TT	56 A8
	94035113	4.00 - 12	3.00 D	2.50 C	4.4	20.9	10.0	61.9	14	9	STD	6	TT	60 A8
Ø 15"	94020843	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	5.5	25.8	12.1	76.8	14	14	STD	4	TT	69 A8
	94020867	5.00 - 15	4.00 E	3.00 D; 4 J; 4½ J	5.5	25.8	12.1	76.8	14	14	STD	6	TT	76 A8
Ø 16"	94034680	4.00 - 16	3.00 D	-	4.4	24.8	11.9	73.9	14	12	STD	4	TT	61 A8
	94020874	5.50 - 16	4.00 E	3.50 D; 4.50 E	5.9	28.0	13.1	83.3	17	19	STD	6	TT	82 A8
	94026449	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	6.7	28.9	13.6	86.2	23	22	SPL	6	TT	85 A8
	94032273	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	6.7	28.9	13.6	86.2	23	24	SPL	8	TT	91 A8
	94020928	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	6.7	28.9	13.6	86.2	23	20	STD	6	TT	85 A8
	94020959	6.00 - 16	4.50 E	4.00 E; 5 K; 5.00 F	6.7	28.9	13.6	86.2	23	23	STD	8	TT	91 A8
	94021024	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	7.1	30.1	14.1	89.8	23	24	STD	6	TT	88 A8
	94021055	6.50 - 16	4.50 E	4.00 E; 5 K; 5.00 F; 5.50 F	7.1	30.1	14.1	89.8	23	26	STD	8	TT	90 A8
	94026463	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	8.1	31.9	14.9	95.0	26	34	SPL	6	TT	94 A8
	94026470	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	8.1	31.9	14.9	95.0	26	36	SPL	8	TT	99 A8
94021086	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	8.1	31.9	14.9	95.0	26	32	STD	6	TT	94 A8	

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

STD: Standard - SPL: Special



Bias



Performance



Steering Control



	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 16"	94021123	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	8.1	31.9	14.9	95.0	26	35	STD	8	TT	99A8
	94029952	7.50 - 16	5.50 F	5.00 F; 5 K; 6.00 F	8.1	31.9	14.9	95.0	26	35	STD	10	TT	101A8
	94038824	9.00 - 16	W 8	6.00 F; W 7; W 8 L	10.1	33.7	15.7	100.3	31	54	SPL	10	TT	108A8
	94021307	9.00 - 16	W 8	6.00 F; W 7; W 8 L	10.1	33.7	15.7	100.3	31	52	STD	8	TT	103A8
	94021338	9.00 - 16	W 8	6.00 F; W 7; W 8 L	10.1	33.7	15.7	100.3	31	52	STD	10	TT	108A8
	94038831	10.00 - 16	W 8	W 8 L	10.8	35.4	16.1	106.9	35	55	SPL	8	TT	110A8
	94038848	10.00 - 16	W 8	W 8 L	10.8	35.4	16.1	106.9	35	56	SPL	10	TT	111A8
	94020720	10.00 - 16	W 8	W 8 L	10.8	35.4	16.1	106.9	35	54	STD	8	TT	110A8
	94032501	10.00 - 16	W 8	W 8 L	10.8	35.4	16.1	106.9	35	56	STD	10	TT	111A8
	94038572	11.00 - 16	W 10 L	W 8; W 8 L	12.6	38.2	17.6	113.8	37	72	SPL	8	TT	114A8
	94055111	11.00 - 16	W 10 L	W 8; W 8 L	12.6	38.2	17.6	113.8	37	74	STD	8	TL	114A8
	94020775	11.00 - 16	W 10 L	W 8; W 8 L	12.6	38.2	17.6	113.8	37	71	STD	8	TT	114A8
Ø 18"	94038589	7.50 - 18	5.50 F	-	8.1	33.9	15.9	100.9	26	34	SPL	6	TT	97A8
	94038596	7.50 - 18	5.50 F	-	8.1	33.9	15.9	100.9	26	37	SPL	8	TT	102A8
	94032600	7.50 - 18	5.50 F	-	8.1	33.9	15.9	100.9	26	39	STD	10	TT	105A8

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance



Steering Control



	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 18"	94021154	7.50 - 18	5.50 F	-	8.1	33.9	15.9	100.9	26	34	STD	6	TT	97 A8
	94021192	7.50 - 18	5.50 F	-	8.1	33.9	15.9	100.9	26	39	STD	8	TT	102 A8
Ø 19"	94020805	4.00 - 19	3.00 D	-	4.5	28.1	13.5	84.4	14	13	STD	4	TT	69 A8
	94020973	6.00 - 19	4.50 E	4.00 E; 5.00 F	6.6	32.1	15.2	96.3	20	22	STD	6	TT	89 A8
Ø 20"	94038800	7.50 - 20	5.50 F	5.00 F	8.1	36.0	17.0	107.3	26	37	SPL	6	TT	99 A8
	94038817	7.50 - 20	5.50 F	5.00 F	8.1	36.0	17.0	107.3	26	42	SPL	8	TT	105 A8
	94021222	7.50 - 20	5.50 F	5.00 F	8.1	36.0	17.0	107.3	26	36	STD	6	TT	99 A8
	94021260	7.50 - 20	5.50 F	5.00 F	8.1	36.0	17.0	107.3	26	41	STD	8	TT	105 A8

STD: Standard - SPL: Special



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference