



IS standard



GROWING TOGETHER

# SM 55 IND-5S



PRODUCT DATA SHEET



Bias



# SM 55 IND-5S

🇬🇧 SM 55 IND-5S has been specially designed for reach stackers and container handlers. Its special abrasion-resistant tread compound provides an extended tire life on asphalt or concrete surfaces and offers excellent stability to vehicles in lift mode.

## Technologies



Extra Deep Tread



Heavy Duty

## Performance



Cut and Chip Resistance



Durability



Hard Surfaces



Stability

	Tire size	Type	PR	LI/SS	Version	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	12.00 - 24	TT	20	-	PORT IND	310	1275	594	3777	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V
Ø 25"	18.00 - 25	TL	40	-	PORT SPL	517	1665	765	5118	13.00/2.5	15.00/2.5

PORT IND: Port Industrial - PORT SPL: Port Special



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference