



AS 504

Description

AS 504 is an agro-industrial tyre mainly designed for soil tillage, implement and material-handling operations. This tyre, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tyre life.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ▪ Telehandler, Industrial & Construction ▪ Telehandler



Version	STANDARD
Tyre Type	TL
Tyre size	11.5/80-15.3
LI/SS	

Dimensions IS Standard

SW (mm)	290
OD (mm)	867
SLR (mm)	380
RC (mm)	2540
Rim Rec	9.00

Load Capacity (IS)

km/h / bar	3.40
10 FR	2730
25 FR	2320
30 FR	2185
40 FR	1950
10 DW	1905
25 DW	1620
30 DW	1525
40 DW	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..