



MP 600

Description

MP 600 is an agro-industrial tire, suitable for municipality/maintenance operations with telehandlers and implement machinery, providing a comfortable driving experience. This tire provides good traction and excellent self-cleaning properties along with an extended product life-cycle.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ▪ Implement Machinery, Industrial & Construction ▪ Telehandler



Version	STANDARD
Tire Type	TL
Tyre size	400/70-24
LI/SS	

Dimensions IS Standard

SW (IS) (mm)	405
OD (IS) (mm)	1185
SLR (IS) (mm)	545
RC (IS) (mm)	3530
Rim Rec	13 SDC
Rim Alt	12

Load Capacity (IS)

km/h / bar	2.50
40 DW	2975
50 DW	2900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..