



AGRIMAX PROCROP



Description

AGRIMAX PROCROP is precisely engineered to meet modern farming demand in row crop and spraying applications. The advanced VF (Very High Flexion) technology allows AGRIMAX PROCROP to carry 40% more load compared to standard tires with same tire pressure. At the same time, the wide footprint of AGRIMAX PROCROP ensures low soil compaction and excellent load distribution that avoids damage to crops.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF270/95R48
LI/SS	155;D

Dimensions IS Standard

SW (IS) (mm)	280
OD (IS) (mm)	1745
SLR (IS) (mm)	815
RC (IS) (mm)	5330
Rim Rec	W9
ECE	E11-106R-0010174

Load Capacity (IS)

km/h / bar	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1660	1875	2085	2260	2510	2650	2895	3145	3355	3530
from 65 to 40	1825	2055	2290	2480	2755	2910	3180	3450	3685	3875
30	1860	2100	2335	2535	2810	2970	3245	3520	3760	3955
20	1895	2140	2380	2580	2865	3025	3305	3590	3830	4030
10	2005	2265	2520	2730	3030	3200	3500	3800	4055	4265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..