



## AT 171

### Description

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

### UM

IS Standard

### Construction

 Bias

### Machinery

Agriculture ■ ATV



Version	STANDARD
Tire Type	TL
Tyre size	30x9-14
LI/SS	77;A8

## Dimensions IS Standard

SW (IS) (mm)	211
OD (IS) (mm)	755
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

## Load Capacity (IS)

km/h / bar	1.40	1.00
40 MUD BOGGING	412	-
80 MUD BOGGING	206	-
40 CASUAL TRANSPORT	-	335
80 CASUAL TRANSPORT	-	170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..