



AGRIMAX RT 945



Description

AGRIMAX RT 945 is specially designed for row crops: it does not damage the crops and preserves the yield. Excellent self-cleaning features allow for a quick change from field operations to road usage, where AGRIMAX RT 945 shows brilliant performance. Its strong carcass gives the tire excellent stability, outstanding traction, and exceptional durability.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TL
Tyre size	320/90R46
LI/SS	146;A8/B

Dimensions IS Standard

SW (IS) (mm)	319
OD (IS) (mm)	1744
SLR (IS) (mm)	810
RC (IS) (mm)	5232
Rim Rec	W 10
Rim Alt	W 9; W 11
ECE	E4-106R-001399
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	1380	1770	2160	2370	2550	2790	3000	-
40	1380	1770	2160	2370	2550	2790	3000	-
30	1480	1895	2315	2540	2730	2990	3210	-
10	1620	2115	2565	3060	3510	3645	4050	4500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..