



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 53



PRODUCT DATA SHEET

EARTHMAX SR 53
RADIAL OTR TIRES



EARTHMAX SR 53 is an All Steel radial tire specially designed for loaders, dozers and low profile dump trucks (LPDT) operating in severe rocky conditions, including underground operations and scrap yards. The deep L-5 tread and the cut-resistant compound provide an extended wear life in addition to excellent traction and stability.



Radial

L-5

A2

274

Technologies



Extra Deep Tread

Performance



Cut Resistance



Durability



Hard Rocky Surface



Stability



Traction

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	17.5 R 25	TL	L-5	*	176 A2	CRC	-	435	1400	637	4214	65	14.00/1.5	-
	17.5 R 25	TL	L-5	**	182 A2	CRC	-	435	1400	637	4214	65	14.00/1.5	-
	17.5 R 25	TL	L-5	***	188 A2	CRC	-	435	1400	637	4214	65	14.00/1.5	-
	17.5 R 25	TL	L-5	**	-	CRC (UMS)	-	435	1400	637	4214	65	14.00/1.5	-
	20.5 R 25	TL	L-5	*	186 A2	CRC	-	535	1550	705	4666	78	17.00/2.0	-
	23.5 R 25	TL	L-5	*	195 A2	CRC	-	604	1666	758	5015	84	19.50/2.5	-
	23.5 R 25	TL	L-5	**	201 A2	CRC	-	604	1666	758	5015	84	19.50/2.5	-
	23.5 R 25	TL	L-5	**	-	CRC (UMS)	-	604	1666	758	5015	84	19.50/2.5	-
	26.5 R 25	TL	L-5	*	202 A2	CRC	-	680	1788	800	5376	95	22.00/3.0	-
	26.5 R 25	TL	L-5	**	209 A2	CRC	-	680	1788	800	5376	95	22.00/3.0	-
	26.5 R 25	TL	L-5	***	214 A2	CRC	-	680	1788	800	5376	95	22.00/3.0	-
	26.5 R 25	TL	L-5	**	-	CRC (UMS)	-	680	1788	800	5376	95	22.00/3.0	-
	29.5 R 25	TL	L-5	*	208 A2	CRC	-	770	1912	859	5755	103	25.00/3.5	-
	29.5 R 25	TL	L-5	**	216 A2	CRC	-	770	1912	859	5755	103	25.00/3.5	-
	29.5 R 25	TL	L-5	**	-	CRC (UMS)	-	770	1912	859	5755	103	25.00/3.5	-

CRC: Cut Resistance Compound - CRC UMS: Cut Resistance Compound (UMS)

In case of underground mine application, consult your servicing dealer or BKT representative

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Radial

L-5

A2

274

Technologies



Extra Deep Tread

Performance



Cut Resistance



Durability



Hard Rocky Surface



Stability



Traction



	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM	
													Rec.	Alt.
Ø 29"	29.5 R 29	TL	L-5	**	218 A2	CRC	-	755	2015	905	6059	102	25.00/3.5	24.00/3.5
	29.5 R 29	TL	L-5	***	223 A2	CRC	-	755	2015	905	6059	102	25.00/3.5	24.00/3.5
	29.5 R 29	TL	L-5	**	-	CRC (UMS)	-	755	2015	905	6059	102	25.00/3.5	24.00/3.5
Ø 33"	35/65 R 33	TL	L-5	**	224 A2	CRC	-	910	2063	915	6215	92	28.00/3.5	-
	35/65 R 33	TL	L-5	***	229 A2	CRC	-	910	2063	915	6215	92	28.00/3.5	-
	35/65 R 33	TL	L-5	**	-	CRC (UMS)	-	910	2063	915	6215	92	28.00/3.5	-
	35/65 R 33 (LPDT) NEWSIZE	TL	L-5	**	-	CRC (UMS)	-	910	2063	915	6215	92	28.00/3.5	-
Ø 39"	45/65 R 39	TL	L-5	**	242 A2	CRC	-	1100	2577	1118	7747	110	36.00/4.5	32.00/4.5
Ø 45"	45/65 R 45	TL	L-5	**	245 A2	CRC	-	1125	2730	1211	8224	112	36.00/4.5	-
	45/65 R 45	TL	L-5	***	250 A2	CRC	-	1125	2730	1211	8224	112	36.00/4.5	-
Ø 51"	50/65 R 51	TL	L-5	**	253 A2	CRC	-	1240	3090	1371	9309	128	40.00/4.5	-
Ø 57"	60/80 R 57	TL	L-5	**	274 A2	CRC	-	1515	3930	1743	11840	118	47.00/5.0	47.00/6.0

CRC: Cut Resistance Compound - CRC UMS: Cut Resistance Compound (UMS)

In case of underground mine application, consult your servicing dealer or BKT representative

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference