



AW 702 IND

Description

AW 702 IND has been developed for Industrial trailers applications. This heavy-duty tire has been designed by BKT to provide a new level of durability.

UM

US Standard

Construction

 Bias

Machinery

Industrial & Construction ■ Trailer



Version	INDUSTRIAL
Tire Type	TT
Tyre size	6.00-16
LI/SS	

Dimensions US Standard

USA Code	94054206
SW (US) (in)	6.7
OD (US) (in)	28.4
SLR (US) (in)	13.3
RC (US) (in)	84.6
Rim Rec	4.00 E
Rim Alt	4.50 E; 4½ K
ECE	E11-106R-004358

Load Capacity (US)

mph / psi	58
5 FR	2700
15 FR	2290
20 FR	2160
25 FR	1930

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..