



FORESTMAX

Description

FORESTMAX is BKT's new radial tire for tractors, which has been mainly developed for forestry applications, but can also be employed for some specific farming operations such as soil milling and stone breaking. Its multi-ply polyester casing and the reinforced sidewall are designed to withstand the harsh forestry operating conditions. In addition, the cut-and-chip resistant tread compound and the steel-belted structure significantly minimize the risk of punctures in the woodland.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STEEL BELTED
Tire Type	TL
Tyre size	540/540R28
LI/SS	149;A8

Dimensions IS Standard

SW (IS) (mm)	550
OD (IS) (mm)	1413
SLR (IS) (mm)	649
RC (IS) (mm)	4247
Rim Rec	W 18 L
ECE	E11-106R-008830

Load Capacity (IS)

km/h / bar	1.2	1.4	1.6	1.8	2.0	2.2	2.4
50	2040	2280	2340	2580	2790	2880	3000
40	2210	2470	2535	2795	3020	3120	3250
30	2370	2645	2715	2995	3235	3345	3480
25	2455	2745	2815	3105	3355	3470	3610
20	2720	3040	3120	3440	3720	3840	4000
15	2965	3310	3395	3745	4050	4185	4355
10	3315	3705	3800	4190	4530	4680	4875
10 forestry service	-	-	-	-	-	-	4000
0 forestry service	-	-	-	-	-	-	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..