



IS standard



GROWING TOGETHER

BK 826



PRODUCT DATA SHEET



Bias



A8



138



BK 826

The BK 826 tire is expertly engineered for trailers in haulage applications, delivering unmatched durability and performance. The 'Harvester Special' version is tailored specifically for harvesting, ensuring optimal reliability in the field. This bias tire boasts a reinforced carcass, offering exceptional load capacity to meet the demands of heavy-duty tasks. Additionally, the BK 826 is available in an "Industrial" variant, designed with superior cut and chip resistance, making it an ideal choice for backhoe loaders in challenging conditions.

Technologies



Reinforced Carcass

Performance



Cut and Chip Resistance



High Load Capacity

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.									
Ø 16"	8.25 - 16	6.50 H	6.00 G	238	863	-	-	STD	8	TT	-	
	8.25 - 16	6.50 H	6.00 G	238	863	-	-	STD	14	TT	-	
	8.25 - 16	6.50 H	6.00 G	238	863	-	-	TR TR	16	TT	134A8	
	8.25 - 16	6.50 H	6.00 G	238	863	-	-	IND	16	TT	-	
	8.25 - 16	6.50 H	6.00 G	238	863	-	-	STD	16	TT	-	
	8.25 - 16	6.50 H	6.00 G	238	863	-	-	IND	18	TT	-	
	8.25 - 16	6.50 H	6.00 G	238	863	-	-	STD	18	TT	-	
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	HAR SPL	12	TT	-	
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	HAR SPL	16	TT	-	
	NEWSIZE											
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	STD	12	TT	-	
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	STD	14	TT	-	
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	IND	16	TT	-	
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	STD	16	TT	-	
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	SR	16	TT	-	
	NEWSIZE											

STD: Standard - TR TR: Tractor Trailer - IND: Industrial - HAR SPL: Harvester Special - SR: Stubble Resistant

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



A8



138

Technologies



Reinforced Carcass

Performance



Cut and Chip Resistance



High Load Capacity



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	9.00 - 16	6.50 H	6.00 G	265	925	-	-	TR TR	18	TT	138 A6
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	TR TR	18	TT	138 A8
	9.00 - 16	6.50 H	6.00 G	265	925	-	-	STD	18	TT	-

STD: Standard - TR TR: Tractor Trailer



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference