



US standard



GROWING TOGETHER

SNOW-RIDE (A)



PRODUCT DATA SHEET



Bias



SNOW-RIDE (A)

SNOW-RIDE is particularly suitable for municipality and maintenance applications in winter conditions with compact loaders and skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks and ensures a longer tire life-cycle.

Technologies



Snow Pattern



Strong Casing

Performance



Durability



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 16"	94040575	12.5/70 - 16	TL	6	-	STD	33.5	12.4	15.2	100.4	26	74	10 LB	-
	94044023	12.5/70 - 16	TL	10	-	STD	33.5	12.4	15.2	100.4	26	76	10 LB	-
Ø 16.5"	94040261	10 - 16.5	TL	6	-	STD	30.7	10.6	14.1	92.1	22	54	8.25	-
	94044009	10 - 16.5	TL	10	-	STD	30.7	10.6	14.1	92.1	22	54	8.25	-
	94043330	12 - 16.5	TL	6	-	STD	32.9	12.0	14.9	98.6	26	65	9.75	-
	94044016	12 - 16.5	TL	10	-	STD	32.9	12.0	14.9	98.6	26	66	9.75	-
Ø 18"	94041398	15.5/60 - 18	TL	10	-	STD	36.9	15.6	16.7	110.8	30	108	W 13	-
Ø 20"	94041381	17.5/65 - 20	TL	10	-	STD	43.1	17.5	19.1	123.0	32	152	W 14 L	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference