



US standard



GROWING TOGETHER

# JUMBO TRAX HD



PRODUCT DATA SHEET



Bias



A8



120

Technologies



Deep Tread

Performance



Cut and Chip Resistance



Durability



Heavy Duty



# JUMBO TRAX HD

JUMBO TRAX HD is a block pattern tire for skid steers. It features cut and chip resistance and is particularly suitable for heavy-duty service. The deep tread along with excellent sidewall protection provides an extended tire life-cycle. JUMBO TRAX HD is also available in a "special" version.

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	S.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 16.5"	94017287	10 - 16.5	TL	10	-	STD	31.3	10.6	14.3	92.3	37	73	8.25	-
	94057313	10 - 16.5	TL	10	120A8	IMP	31.3	10.6	14.3	92.3	37	72	8.25	-
	94031863	10 - 16.5	TL	10	-	SPL	31.3	10.6	14.3	92.3	37	73	8.25	-
	94029549	12 - 16.5	TL	12	-	STD	33.7	12.8	15.2	99.3	43	93	9.75	-
	94017294	12 - 16.5	TL	10	-	STD	33.7	12.8	15.2	99.3	43	94	9.75	-

IMP: Implement - SPL: Special - STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference