



AGRIMAX V-FLECTO



AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tyre is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tyres, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tyre. BKT has designed this tyre with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

US Standard

 Radial

Agriculture ■ High-Power Tractor

STEEL BELTED SPL

TL

VF710/70R42

undefined US Standard

94075829

28.3

81.0

36.5

245.4

DW 25 B

DW 23 B; DW 24 B

E11-106R-009053

mph / psi	9	12	15	17	20	23	29	35	41	46
45	8540	9920	11310	12930	14310	15700	17310	18230	20070	21690
from 40 to 25	9380	10900	12420	14200	15720	17240	19010	20030	22060	23830
20	9580	11120	12680	14480	16040	17590	19400	20440	22510	24320
12	9770	11340	12930	14770	16360	17930	19770	20830	22950	24790
5	10330	11990	13670	15620	17290	18970	20920	22030	24270	26220
Upto 20 Cyc	10650	12380	14100	16110	17850	19560	21580	22730	25030	27050
Upto 10 Cyc	12710	14770	16830	19230	21300	23360	25760	27140	29880	32300
Upto 5Cyc	13930	16190	18450	21090	23350	25610	28240	29740	32760	35390
5 HT	9580	11120	12680	14480	16040	17590	19400	20440	22510	24320

25-02-2026