



US standard



GROWING TOGETHER

# TR 319



PRODUCT DATA SHEET



Bias



116

Performance



Self-Cleaning



Stability



Traction



# TR 319

TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden, municipality and soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet surfaces, where stability and self-cleaning properties are required.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 12"	94043637	26 X 12.00 - 12	10.50 AT	8.0 AT; 8.5 AT; 9.0 AT	12.5	25.2	11.4	75.1	23	41	STD	8	TL	116 A3
Ø 15"	94051601	29 X 12.50 - 15	10 LB	-	12.3	29.7	14.2	89.1	24	44	STD	6	TL	98 B
	94053247	29 X 12.50 - 15	10 LB	-	12.3	29.7	14.2	89.1	24	49	STD	8	TL	106 B

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference