



EARTHMAX SR 47 TP

Description

EARTHMAX SR 47 TP (E-4) is an All-Steel radial tire specially engineered for rigid haul trucks operating in conditions requiring maximum traction and puncture resistance. The E-4 tread depth ensure long wear even on long hauls, thus reducing downtime and increasing productivity. EARTHMAX SR 47 TP is perfect for any task demanding both traction and stability particularly on muddy or slippery terrain. Available in standard and cut-resistant compounds.



UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	24.00R35
LI/SS	209;B

Dimensions IS Standard

OD (IS) (mm)	2185
SLR (IS) (mm)	985
RC (IS) (mm)	6625
Rim Rec	17.00/3.5
TRA Code	E4

Load Capacity (IS)

km/h / bar	5.00	5.25	5.50	5.75	6.00	6.25	6.50	6.75	7.00
50	14000	14500	15500	16000	16500	17000	17500	18000	18500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..