



## AGRIMAX SIRIO



### Description

AGRIMAX SIRIO is a high-speed tire (up to 70 km/h - 45 mph) developed for high-performance tractors. Its design is perfect for both haulage and soil tillage applications. The high sidewall flexibility ensures outstanding stability, handling and comfort to improve the driving experience. It is also available with IF technology that allows to carry heavy loads at a low inflating pressure. The reinforced casing and the high number of belts guarantee great traction on the field.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ High-Power Tractor

Version HIGH SPEED

Tire Type TL

Tyre size 540/65R34

LI/SS 152;D

## Dimensions US Standard

USA Code	94045297
SW (US) (in)	20.9
OD (US) (in)	61.7
SLR (US) (in)	28.4
RC (US) (in)	186.4
Rim Rec	W 16 L
Rim Alt	W 18
ECE	E4-106R-000815
TRA Code	R1W

## Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
45	3370	3870	4440	5020	5590	6160	6670	7160
40	3680	4230	4860	5480	6110	6730	7290	7830
30	3870	4440	5100	5760	6420	7080	7650	8220
25	4030	4640	5320	6010	6690	7390	7980	8580
15	4360	5020	5760	6500	7240	7990	8640	9280
5	5520	6350	7290	8220	9160	10100	10920	11740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..