



COMMANDER (F)



Description

COMMANDER (F) is a front 3-rib pattern tire - perfect for soil tillage and haulage applications. Its deep tread made of a cut-and-chip resistant compound ensures a longer tire life, together with high load capacity.

UM

US Standard

Construction

⌘ Bias

Machinery

Agriculture ■ 2WD Tractor

Version	STANDARD
Tire Type	TT
Tyre size	6.00-16
LI/SS	91;A8

Dimensions US Standard

USA Code	94045150
SW (US) (in)	6.9
OD (US) (in)	29.5
SLR (US) (in)	14.1
RC (US) (in)	90.9
Rim Rec	4.50 E
Rim Alt	4.00 E; 5.00 F
ECE	E11-106R-003001
TRA Code	F2

Load Capacity (US)

mph / psi	68
25	1360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..