



TR 270

Description

TR 270 is a tractor tire suitable for soil tillage applications. It is specially designed for providing maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning features. TR 270 perfectly meets all these characteristics.

UM

US Standard

Construction

◇◇ Bias

Machinery

Agriculture ■ Tractor



Version	STANDARD
Tire Type	TT
Tyre size	23.1-30
LI/SS	143;A8

Dimensions US Standard

USA Code	94004911
SW (US) (in)	23.2
OD (US) (in)	68.8
SLR (US) (in)	31.1
RC (US) (in)	205.8
Rim Rec	DW 20 A; DW 20 B
TRA Code	R2

Load Capacity (US)

mph / psi	16
25	6000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..