



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 459



PRODUCT DATA SHEET

EARTHMAX SR 459

RADIAL OTR TIRES



EARTHMAX SR 459 is an All-Steel radial tire for rigid dump trucks operating in quarries and open pit mines. Its specifically developed symmetric design ensures excellent durability on both rear and front axles. The multiple steel belts provide superior protection against shocks and rock penetration, whilst the high tread depth ensures optimal protection to the carcass and a long tire life. In addition, the close tread design maximizes ground contact resulting in excellent stability as well as great operator comfort. EARTHMAX SR 459 stands out for excellent traction on any ground, even on muddy surfaces.



Radial



Technologies



All Steel Radial



Extra Deep Tread



Heavy Duty



Strong Casing



Reinforced Carcass

Performance



Durability



Cut and Chip Resistance



Hard Rocky Surface



Handling and Comfort



Traction

Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM		
												Rec.	Alt.	
Ø 49"	27.00 R 49	TL	E-4	**	223 B	CRC	409	746	2720	1231	8245	81	19.50/4.0	-
	27.00 R 49	TL	E-4	**	223 B	STDC	474	746	2720	1231	8245	81	19.50/4.0	-
	27.00 R 49	TL	E-4	**	223 B	HRC	523	746	2720	1231	8245	81	19.50/4.0	-

CRC: Cut Resistance Compound - STDC: Standard Compound - HRC: Heat Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference