



IS standard



GROWING TOGETHER

# AW 729



PRODUCT DATA SHEET



Bias



A8



149

### Performance



Reduced Soil Compaction



Self-Cleaning



Durability



On/Off Road



# AW 729

AW 729 is an agricultural tire specifically designed for transport, hay harvesting, baling and soil tillage applications. Its rounded shoulder and three central grooves tread design provide low soil compaction and avoids damages to the field. AW 729 is the ideal tire for modern farming, and it is suited for both on-and-off-the-road usage.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS	
		Rec.	Alt.								DW	FR
Ø 16"	340/55 - 16 (13.0/55 - 16)	11.0	-	343	785	358	2358	STD	-	TL	121 A8	133 A8
Ø 17"	15.0/55 - 17	13.00	13; W 13	385	850	377	2560	STD	10	TL	122 A8	134 A8
	380/55 - 17	13.00	13; W 13	385	850	377	2560	STD	-	TL	122 A8	134 A8
	480/45 - 17	16.00	-	480	866	400	2526	STD	-	TL	134 A8	146 A8
	500/50 - 17	16.00	-	500	945	426	2885	STD	-	TL	137 A8	149 A8

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling