



IS standard



GROWING TOGETHER

D 404



PRODUCT DATA SHEET



Bias



D 404

D 404 is a road-oriented tire ideal for transport applications with trailers and light trucks. An excellent grip on the road along with regular wear turns into extra durability.

Performance



Durability



Road Oriented

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 14"	6.00 - 14	4.5 J	4 J; 5 J	170	690	-	-	STD	8	TT	-
	6.50 - 14	4.5 J	-	175	695	-	-	STD	8	TT	-
	6.50 - 14	4.5 J	-	175	695	-	-	STD	10	TT	-
Ø 15"	7.00 - 15	5.50 F	5 K	198	760	-	-	STD	8	TT	-
	7.00 - 15	5.50 F	5 K	198	760	-	-	STD	10	TT	-
	7.00 - 15	5.50 F	5 K	198	760	-	-	STD	12	TT	-
	7.50 - 15	6.00	-	220	785	-	-	STD	12	TT	-
	7.50 - 15	6.00	-	220	785	-	-	STD	14	TT	-
Ø 16"	7.00 - 16	5.50 F	6.00 G	198	785	-	-	STD	12	TT	-
	7.00 - 16	5.50 F	6.00 G	198	785	-	-	STD	10	TT	-
	7.00 - 16	5.50 F	6.00 G	198	785	-	-	STD	16	TT	-
	7.50 - 16	6.00 G	5.50 F	212	820	-	-	STD	14	TT	-
	7.50 - 16	6.00 G	5.50 F	212	820	-	-	STD	8	TT	-

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias

Performance



Durability



Road Oriented



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	7.50 - 16	6.00 G	5.50 F	212	810	-	-	STD	12	TT	-
	7.50 - 16	6.00 G	5.50 F	212	810	-	-	STD	16	TT	-
	7.50 - 16	6.00 G	5.50 F	212	810	-	-	STD	10	TT	-
	8.25 - 16	6.50 H	6.00 G	238	858	-	-	STD	8	TT	-
	8.25 - 16	6.50 H	6.00 G	238	858	-	-	STD	14	TT	-
	8.25 - 16	6.50 H	6.00 G	238	858	-	-	STD	16	TT	-
	8.25 - 16	6.50 H	6.00 G	238	858	-	-	STD	18	TT	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference