



FL 630 SUPER

Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ▪ Spreader

Version	STANDARD
Tire Type	TL
Tyre size	580/65R22.5
LI/SS	174;D

Dimensions IS Standard

SW (IS) (mm)	582
OD (IS) (mm)	1326
SLR (IS) (mm)	594
RC (IS) (mm)	4058
Rim Rec	AG 18.00
Rim Alt	AG 16.00; AG 17.00; AG 20.00
ECE	E11-106R-008289

Load Capacity (IS)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.5	5.0	5.5	6.0
70	1955	2440	2745	3175	3600	3965	4335	4760	5065	5370	5735	6100
65	2145	2680	3015	3485	3955	4355	4760	5230	5565	5900	6300	6700
50	2600	3245	3650	4220	4785	5275	5760	6330	6735	7140	7625	8110
40	2920	3650	4105	4740	5380	5925	6475	7110	7570	8025	8570	9115
25	3390	4240	4770	5510	6250	6885	7520	8265	8790	9320	9955	10590
10	3860	4825	5430	6275	7120	7840	8565	9410	10010	10615	11340	12060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..