



US standard



GROWING TOGETHER

# AT 523



PRODUCT DATA SHEET



Bias



# AT 523

BKT's AT 523 is a multifunctional tire designed to provide reliable performance in agricultural, turf, and industrial applications. Its tread design ensures excellent traction and self-cleaning capabilities, which are key features for tackling a variety of surfaces: from rammed earth and turf to hard surfaces typical of industrial settings. The flatter profile and enlarged center block, combined with the R-1 and R-4 type design, provide greater stability on the road, while the rounded shoulders protect the turf, preserving its integrity even under intensive operating conditions. The strong carcass and a cut-resistant tread compound make AT 523 particularly durable. This combination of ruggedness, versatility and ease of use makes AT 523 the ideal solution for those who need a single tire that can cope with a variety of situations: from soil preparation and lawn operations to industrial use.

**Technologies**



Strong Casing



Rounded Shoulder Technology

**Performance**



Traction



Self-Cleaning



Hard Surfaces



Ideal for grassland



Stability

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 12"	94512522	26 X 12.00 - 12	10.50 I - 55 ; I - 70 ; I - 90	10½ JA ; 8½ JA	11.8	25.6	11.8	74.7	17	36	STD	6	TL	107A8

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - SLR ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference