



## AGRIMAX FORCE



### Description

AGRIMAX FORCE the high-end product of BKT specially designed for soil tillage, haulage and applications with high-power tractors and harrows for top performance and efficiency. Thanks to its low rolling resistance, the tire can carry heavy loads with a lower inflation pressure compared to a standard tire reducing soil compaction. AGRIMAX FORCE features a reinforced bead and provides excellent self-cleaning properties and fuel economy.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Harvester

Version	STANDARD
Tire Type	TL
Tyre size	IF900/50R42
LI/SS	180;D

## Dimensions IS Standard

SW (IS) (mm)	881
OD (IS) (mm)	1955
SLR (IS) (mm)	872
RC (IS) (mm)	5830
Rim Rec	DW 30 B
Rim Alt	TW 30 B
ECE	E11-106R-006492
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4										
<b>70</b>	3345	3855	4440	4950	5530	6040	6770	7280										
<b>From</b>																		
<b>65 to</b>	3680	4240	4880	5440	6080	6640	7440	8000										
<b>40</b>																		
<b>30</b>	3825	4405	5075	5655	6320	6905	7735	8320										
<b>20</b>	3970	4575	5270	5875	6565	7170	8035	8640										
<b>10</b>	4670	5380	6195	6905	7720	8430	9445	10160										
<b>Upto</b>																		
<b>30</b>	4780	5510	6340	7070	7900	8630	9670	10400										
<b>Cyc</b>																		
<b>Upto</b>																		
<b>15</b>	5700	6570	7560	8430	9420	10290	11530	12400										
<b>Cyc</b>																		
<b>Upto</b>																		
<b>10</b>	6255	7205	8295	9245	10335	11285	12645	13600										
<b>Cyc</b>																		
<b>10HT</b>	3825	4405	5075	5655	6320	6905	7735	8320										

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors, omissions and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to reproduce or use the content of this publication for any purpose other than that intended.

reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic or otherwise without prior written consent by Balkrishna Industries Ltd..