



EM 936

Description

EM 936 has been specially designed for excavators and telehandlers in digging and loading operations. Besides, one size is particularly suitable for graders and loaders in grading, loading and transport applications. EM 936 features outstanding riding comfort and enhanced self-cleaning properties. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions. Its "special" version is made of a special compound.



UM

IS Standard

Construction

 Bias

Machinery

Industrial & Construction ■ Excavator

Version STANDARD

Tire Type TL

Tyre size 20-24

LI/SS 158;B

Dimensions IS Standard

OD (IS) (mm)	1390
SLR (IS) (mm)	665
RC (IS) (mm)	4205
Rim Rec	16.00 T SDC
TRA Code	E2/G2/L2

Load Capacity (IS)

km/h / bar	2.50	3.00
50	4250	-
10	-	6500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..