



## AGRIMAX RT 765



### Description

AGRIMAX RT 765, a BKT 70 series tyre, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tyre provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tyre Type	TL
Tyre size	480/70R24
LI/SS	138;D

## Dimensions IS Standard

SW (mm)	479
OD (mm)	1316
SLR (mm)	583
RC (mm)	3900
Rim Rec	W 15 L
Rim Alt	W 14 L; W 16 L
ECE	E11-106R-005519
TRA Code	R1W

## Load Capacity (IS)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4
65	2730	3135	3600	4060	4525	4990	5455	5800
50	2865	3290	3780	4265	4755	5240	5725	6090
40	2990	3435	3945	4450	4960	5470	5975	6355
30	3135	3605	4140	4670	5205	5740	6270	6670
10 LT	3655	4200	4825	5445	6065	6690	7310	7775
10HT	3135	3605	4140	4670	5205	5740	6270	6670

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..