



AW 708

Description

AW 708 has been developed for soil tillage, transport and hay harvesting applications with implement machinery, trailers and balers. An HD version is available with a special cut-and-chip resistant compound.

UM

US Standard

Construction

◆ Bias

Machinery

Agriculture ▪ Baler, Industrial & Construction ▪ Trailer



Version STUBBLE RESISTANT

Tire Type TL

Tyre size 19.0/45-17

LI/SS

Dimensions US Standard

USA Code	94047697
SW (US) (in)	18.5
OD (US) (in)	34.1
SLR (US) (in)	15.0
RC (US) (in)	99.8
Rim Rec	16.00
ECE	E11-106R-003636

Load Capacity (US)

mph / psi	57
5 FR	10960
15 FR	9310
20 FR	8760
25 FR	7830

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..