



AGRIMAX FORTIS



Description

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and powerful tractors, it allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version SPECIAL

Tire Type TL

Tyre size 600/70R30

LI/SS 158;D

Dimensions IS Standard

SW (IS) (mm)	611
OD (IS) (mm)	1602
SLR (IS) (mm)	724
RC (IS) (mm)	4810
Rim Rec	DW 20 B
Rim Alt	DW 18 L; W 18 L
ECE	E4-106R-001400
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	2040	2380	2680	2975	3275	3530	3910	4250
50	2145	2505	2815	3130	3440	3710	4110	4465
40	2220	2590	2915	3240	3565	3840	4255	4625
30	2350	2740	3085	3425	3770	4060	4500	4890
10 LT	2735	3190	3590	3990	4390	4730	5240	5695
10 HT	2350	2740	3085	3425	3770	4060	4500	4890

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..