



IS standard



GROWING TOGETHER

TR 463



PRODUCT DATA SHEET



Bias



Performance



Traction



TR 463

TR 463 has been specially designed for backhoe loaders and industrial tractors. Made of a superior tread compound and featuring a strong nylon casing, this tire stands for best results in industrial and OTR applications, and on construction sites. TR 463 provides excellent traction for drive wheels.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	16.9 - 24	TL	12	149 A8	IND	445	1300	584	3877	DW 15 L	DW 14 L
	16.9 - 24	TL	14	152 A8	IND	445	1300	584	3877	DW 15 L	DW 14 L
	NEWSIZE										
Ø 26"	18.4 - 26	TL	12	156 A8	IND	480	1425	637	4215	DW 16 L	DW 15 L
	18.4 - 26	TL	14	158 A8	IND	480	1425	637	4215	DW 16 L	DW 15 L
	NEWSIZE										
Ø 28"	16.9 - 28	TL	12	152 A8	IND	450	1405	636	4190	DW 15 L	DW 14 L

IND: Industrial



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference