



AGRIMAX TURF RT 333

Description

AGRIMAX TURF RT 333 is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures self-cleaning properties and allows for significant fuel saving.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Vineyard Harvester

Version	STANDARD
Tire Type	TL
Tyre size	280/70R18
LI/SS	114;A8

Dimensions IS Standard

SW (IS) (mm)	289
OD (IS) (mm)	840
SLR (IS) (mm)	390
RC (IS) (mm)	2550
Rim Rec	W 9
Rim Alt	W 8; W 10
ECE	E11-106R-006473

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	555	640	735	830	925	1015	1110	1180
40	555	640	735	830	925	1015	1110	1180
30	595	685	785	890	990	1090	1190	1265
10 LT	745	860	985	1110	1240	1365	1490	1585
10 HT	595	695	785	890	990	1090	1190	1265

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..