



## AGRIMAX PROCROP



### Description

AGRIMAX PROCROP is precisely engineered to meet modern farming demand in row crop and spraying applications. The advanced VF (Very High Flexion) technology allows AGRIMAX PROCROP to carry 40% more load compared to standard tires with same tire pressure. At the same time, the wide footprint of AGRIMAX PROCROP ensures low soil compaction and excellent load distribution that avoids damage to crops.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Sprayer

Version STEEL BELTED

Tire Type TL

Tyre size VF270/95R48

LI/SS 155;D

## Dimensions US Standard

USA Code	94076178
SW (US) (in)	11.0
OD (US) (in)	68.7
SLR (US) (in)	32.1
RC (US) (in)	209.8
Rim Rec	W9
ECE	E11-106R-0010174

## Load Capacity (US)

mph / psi	14	17	20	23	29	35	41	46	52	58
<b>45</b>	3660	4140	4600	4990	5540	5850	6390	6940	7400	7790
<b>from 40 to 25</b>	4030	4540	5050	5470	6080	6420	7020	7610	8130	8550
<b>20</b>	4110	4630	5150	5590	6200	6550	7160	7760	8290	8720
<b>12</b>	4180	4720	5250	5690	6320	6670	7290	7920	8450	8890
<b>5</b>	4430	5000	5560	6020	6680	7060	7720	8380	8940	9410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..