



AGRIMAXFACTOR

Description

AGRIMAXFACTOR is BKT's brand-new 70 series for tractors perfect for haulage and soil tillage operations. The improved tread design with increased lug length and changed lug orientation stands for better roadability. The reduced lug angle ensures less rolling resistance. AGRIMAXFACTOR's overall advantages are great handling in combination with driving comfort and excellent durability. The exclusive sidewall shows the "E-READY" logo that highlights BKT's commitment to electric mobility.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version STANDARD

Tire Type TL

Tyre size 420/70R28

LI/SS 133;D

Dimensions US Standard

| | |
|---------------|-----------------|
| USA Code | 94070633 |
| SW (US) (in) | 16.5 |
| OD (US) (in) | 53.1 |
| SLR (US) (in) | 23.9 |
| RC (US) (in) | 157.5 |
| Rim Rec | W 13 |
| Rim Alt | W 12; W 14 L |
| ECE | E11-106R-007652 |
| TRA Code | R1W |

Load Capacity (US)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|------|------|------|------|------|
| 40 | 2500 | 2910 | 3320 | 3730 | 4130 | 4540 |
| 30 | 2630 | 3060 | 3490 | 3920 | 4350 | 4770 |
| 25 | 2740 | 3200 | 3640 | 4090 | 4540 | 4980 |
| 20 | 2880 | 3350 | 3820 | 4290 | 4760 | 5220 |
| 5 LT | 3360 | 3900 | 4450 | 5000 | 5560 | 6100 |
| 5 HT | 2880 | 3350 | 3820 | 4290 | 4760 | 5220 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..