



EM 937 (E3)



Description

EM 937 (E-3) has been specially designed for rigid dumpers in surface mining applications. It features excellent durability and provides high cut and chip resistance. EM 937 (E-3) is particularly suitable for heavy duty service.

UM

US Standard

Construction

◆ Bias

Machinery

OTR ■ Rigid Dump Truck

Version STANDARD

Tire Type TL

Tyre size 14.00-25

LI/SS

Dimensions US Standard

USA Code	94015450
OD (US) (in)	53.9
SLR (US) (in)	24.4
RC (US) (in)	161.6
Rim Rec	10.00/1.5
TRA Code	E3/L3

Load Capacity (US)

mph / psi	94	134
30	12300	-
5	-	22000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..