



RT 747 AGRO INDUSTRIAL



Description

RT 747 AGRO INDUSTRIAL is a radial agro-industrial tire suitable for compact loaders and telehandlers. Its extra wide lugs provide excellent traction and great stability in lifting operations. It has been designed with a special cut-and-chip resistance compound that enables the tire to carry heavy loads. RT 747 AGRO INDUSTRIAL is the right answer to all general farming operations that need outstanding versatility.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ▪ Compact Loader, Industrial & Construction ▪ Compact Loader

| | |
|-----------|-----------|
| Version | STANDARD |
| Tire Type | TL |
| Tyre size | 460/70R24 |
| LI/SS | 159;A8 |

Dimensions IS Standard

| | |
|---------------|------------------|
| SW (IS) (mm) | 465 |
| OD (IS) (mm) | 1254 |
| SLR (IS) (mm) | 556 |
| RC (IS) (mm) | 3840 |
| Rim Rec | DW 15 L |
| Rim Alt | DW 14 L; DW 16 L |
| ECE | E11-106R-005105 |

Load Capacity (IS)

| km/h / bar | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.5 | 4.0 |
|------------|------|------|------|------|------|------|------|-------|
| 50 | 1535 | 1890 | 2245 | 2560 | 2915 | 3265 | 3505 | 4000 |
| 40 | 1705 | 2100 | 2495 | 2845 | 3240 | 3630 | 3895 | 4375 |
| 30 | 1775 | 2185 | 2595 | 2960 | 3370 | 3775 | 4050 | 4550 |
| 25 | 1805 | 2225 | 2645 | 3015 | 3435 | 3850 | 4130 | 4640 |
| 10 Cyc | 2560 | 3150 | 3745 | 4270 | 4860 | 5445 | 5845 | 6565 |
| Static | 3920 | 4830 | 5740 | 6545 | 7450 | 8350 | 8960 | 10065 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..