



## EARTHMAX SR 30



### Description

EARTHMAX SR 30 (E-3/L-3) is an All Steel radial tire which is dual-purposed for loaders and articulated dump trucks. The multi-layer steel belts and the rigid block pattern provide excellent traction, stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of harsh operating conditions.

### UM

IS Standard

### Construction

 Radial

### Machinery

OTR ■ Articulated Dump Truck

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	29.5R25
LI/SS	200;B

## Dimensions IS Standard

OD (IS) (mm)	1861
SLR (IS) (mm)	818
RC (IS) (mm)	5555
Rim Rec	25.00/3.5
TRA Code	E3

## Load Capacity (IS)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	11500	11800	12500	12850	13600	14000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..