



LOADER SPECIAL

Description

LOADER SPECIAL (L-5) is a bias-ply tire that keeps your loaders on the move and provides top efficiency in heavy-duty rock operations. Optimum traction and exceptional cut resistance will boost productivity.

UM

IS Standard

Construction

⌘ Bias

Machinery

OTR ■ Dozer



Version	STANDARD
Tire Type	TL
Tyre size	29.5-25
LI/SS	

Dimensions IS Standard

OD (IS) (mm)	1930
SLR (IS) (mm)	884
RC (IS) (mm)	5753
Rim Rec	25.00/3.5
TRA Code	L5

Load Capacity (IS)

km/h / bar	4.25
10	17500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 27-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..