



US standard



GROWING TOGETHER

DON 2000



PRODUCT DATA SHEET



Bias



DON 2000

DON 2000 is a suitable for transport operations with trailers and light trucks both on and off the road. It ensures extra durability along with high performance during the entire product life-cycle.

Performance



Durability



On/Off Road

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 16"	94013876	7.50 - 16	6.00 G	5.50 F	8.5	33.1	-	-	23	57	STD	16	TT	-
Ø 20"	94022571	9.00 - 20	7.0	6.5 ; 7.5	10.6	41.3	-	-	27	106	STD	16	TT	-
	94045495	9.00 - 20	7.0	6.5 ; 7.5	10.6	41.3	-	-	27	109	TRTR	16	TT	-
	94040858	10.00 - 20	7.5	7.0 ; 8.0	11.3	42.5	-	-	28	119	INDTR	16	TT	-
	94043866	10.00 - 20	7.5	7.0 ; 8.0	11.3	42.5	-	-	28	120	INDTR	18	TT	-
	94067725	11.00 - 20	8.0	7.5 ; 8.5	11.5	43.7	20.5	134.4	28	131	STD	18	TT	-
	94022540	12.00 - 20	8.5	8.0 ; 9.0	12.4	45.1	21.1	138.5	28	142	STD	18	TT	-
Ø 24"	94022557	12.00 - 24	8.5	8.0 ; 9.0	12.4	49.0	-	-	28	150	STD	18	TT	-

STD: Standard - TR TR: Tractor Trailer - IND TR: Industrial Trailer



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference