



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor

Version SPECIAL

Tire Type TL

Tyre size 520/70R38

LI/SS 164;D

Dimensions US Standard

USA Code	94516124
SW (US) (in)	21.1
OD (US) (in)	68.9
SLR (US) (in)	30.4
RC (US) (in)	205.2
Rim Rec	DW 18 L
ECE	E11-106R-0011692
TRA Code	R1W

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29
45	5020	5820	6620	7530	8330	9140	10030
from 40 to 25	5510	6390	7270	8270	9150	10030	11020
20	5620	6530	7430	8430	9340	10240	11240
12	5730	6660	7570	8600	9520	10440	11460
5	6060	7030	8000	9090	10060	11030	12120
5 HT	5620	6520	7420	8430	9330	10230	11240
Upto 5 Cyc	8190	9500	10810	12280	13590	14900	16370
Upto 10 Cyc	7470	8660	9870	11210	12400	13600	14940
Upto 20 Cyc	6260	7260	8270	9390	10390	11390	12510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..