



EARTHMAX SR 55

Description

EARTHMAX SR 55 is an All Steel Radial tire specially designed for loaders and load haul dumps operating in the most severe underground mining operations, and at scrapyards. Thanks to excellent cut protection resulting from the extra-deep and smooth tread design, EARTHMAX SR 55 is able to achieve peak productivity with reduced downtime along with excellent durability. Equipment operators will also appreciate extraordinary stability.



UM

US Standard

Construction

 Radial

Machinery

OTR ■ Dozer

Version	CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	18.00R25
LI/SS	206;A2

Dimensions US Standard

USA Code	94515233
OD (US) (in)	65.6
SLR (US) (in)	28.9
RC (US) (in)	191.0
Rim Rec	13.00/2.5
TRA Code	L5S

Load Capacity (US)

mph / psi	80	83	87	91	94	98	102	105	109	112	116	120	123	127	131
5	26000	26800	27600	28300	29100	30000	30900	32000	33100	33100	34200	35300	36400	36400	37500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..