



IS standard



GROWING TOGETHER

BK-LOADER 53



PRODUCT DATA SHEET



Radial



155



BK-LOADER 53

BK-LOADER 53 is an aramid-belted tire designed for loaders in industrial applications. The unique tread design provides best lateral stability in addition to extended tread wear and extraordinary resistance against cuts and punctures thanks to the extra deep tread. BK-LOADER 53 features outstanding self-cleaning properties as well as excellent grip and traction on both wet and dry surfaces. This tire is particularly suitable for recycling operations.

Technologies



Aramid Belted

Performance



Cut and Chip Resistance



High Puncture Resistance



Self-Cleaning



Traction

	Tire size	Type	STAR RATING	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 18"	365/70 R 18	TL	-	146 A2/142 A4	AB	360	990	458	3017	11	-
	405/70 R 18	TL	-	153 A2/149 A4	AB	407	1045	-	-	13	14; 13 SDC; 12; 12 SDC
Ø 20"	405/70 R 20	TL	-	155 A2/151 A4	AB	407	1097	511	3339	13	14; 13 SDC; 12; 12 SDC

AB: Aramid Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference