



US standard



GROWING TOGETHER

# EARTHMAX

RADIAL OTR TIRES

## SR 475



PRODUCT DATA SHEET



Radial



# EARTHMAX SR 475

RADIAL OTR TIRES



EARTHMAX SR 475 is an all steel radial tire specially designed for Rigid Dump Trucks. It is ideal for hard and rocky operations especially with long hauls. The unique tread design generate lower heat in hot climate and provides excellent traction. Its strong all steel casing and belts provide great stability and resistant to snags and punctures. EARTHMAX SR 475 has been developed with squared shoulder that ensures excellent maneuverability and handling, maximizing the ground contact.

### Technologies



### Performance



	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 33"	94064397	18.00 R 33	TL	**	191 B	CRC	E-4	182	73.2	19.3	33.9	225.2	63	1021	13.00/2.5	-
	94064854	18.00 R 33	TL	***	195 B	CRC	E-4	182	73.2	19.3	33.9	225.2	63	1058	13.00/2.5	-
	94064861	18.00 R 33	TL	***	195 B	STDC	E-4	200	73.2	19.3	33.9	225.2	63	1047	13.00/2.5	-
Ø 35"	94066933	24.00 R 35	TL	**	209 B	CRC	E-4	243	85.0	25.7	38.2	259.4	74	1695	17.00/3.5	-
	94066940	24.00 R 35	TL	**	209 B	STDC	E-4	289	85.0	25.7	38.2	259.4	74	1677	17.00/3.5	-

CRC: Cut Resistance Compound - STDC: Standard Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference