



IS standard



GROWING TOGETHER

SIERRAMAX

ATV & GO KART TIRES



PRODUCT DATA SHEET



Radial



58



SIERRA MAX
ATV & GO KART TIRES

UK SIERRA MAX is the BKT tire for both all-terrain and lawn and garden applications. Its radial construction provides a significantly smoother and more comfortable ride over extreme terrains such as deserts, or dirty and rocky surfaces. The special tread design along with its wider footprint provides outstanding forward and lateral traction.

Technologies



M+S

Performance



Comfort



Sport



Traction

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 12"	AT 25 X 8 R 12	43 N	6.5	-	206	640	292	1899	-	STD
	AT 25 X 10 R 12	50 N	8.0	-	260	640	294	1923	-	STD
	AT 26 X 9 R 12	49 N	7.0	-	230	660	304	2009	-	STD
	NEWSIZE									
	AT 26 X 10 R 12	52 N	8.0	-	260	660	306	2006	-	STD
	NEWSIZE									
	AT 26 X 11 R 12	55 N	9.0	-	280	660	301	1994	-	STD
NEWSIZE										
AT 26 X 12 R 12	58 N	9.5	-	305	660	303	1998	-	STD	
NEWSIZE										
Ø 14"	AT 26 X 9 R 14	48 N	7.00	-	230	675	307	2005	-	STD
	AT 26 X 11 R 14	54 N	9.00	-	280	675	310	2027	-	STD
	AT 27 X 9 R 14	50 N	7.00	-	230	700	316	2070	-	STD
	AT 27 X 11 R 14	56 N	9.00	-	280	700	318	2091	-	STD

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index