



AGRIMAX TURF RT 333



Description

AGRIMAX TURF RT 333 is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures self-cleaning properties and allows for significant fuel saving.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Vineyard Harvester

Version	STANDARD
Tire Type	TL
Tyre size	200/65R16
LI/SS	94;A8/B

Dimensions US Standard

USA Code	94070640
SW (US) (in)	8.0
OD (US) (in)	26.2
SLR (US) (in)	12.2
RC (US) (in)	78.7
Rim Rec	W6
ECE	E11-106R-007678

Load Capacity (US)

mph / psi	9	12	15	17	20	23	29	35
30	700	820	940	1040	1150	1240	1380	1480
25	700	820	940	1040	1150	1240	1380	1480
20	750	890	1010	1120	1230	1330	1480	1590
5 LT	940	1100	1260	1390	1540	1660	1860	1990
5 HT	750	890	1010	1120	1230	1330	1480	1590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..