



AT 625

Description

AT 625 is suitable for backhoe loaders and compact loaders in all farming digging and loading operations. Its extra deep tread ensures increased puncture resistance and durability. AT 625 features excellent traction and stability as well as improved cut and chip resistance.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Harvester, Industrial & Construction ■
Backhoe Loader



Version	STANDARD
Tire Type	TL
Tyre size	14.9-24
LI/SS	145;A8

Dimensions IS Standard

SW (IS) (mm)	400
OD (IS) (mm)	1265
SLR (IS) (mm)	575
RC (IS) (mm)	3800
Rim Rec	DW 13
Rim Alt	DW 11; DW 12; DW 13 L
TRA Code	R4

Load Capacity (IS)

km/h / bar	2.90
40	2900

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..