



US standard



GROWING TOGETHER

MP 585



PRODUCT DATA SHEET



Bias



A8



38

Technologies



High Speed



Block Pattern

Performance



Durability



Stability



MP 585

MP 585 is an agro-industrial tire, which is suitable for multi-purpose vehicles in municipality/maintenance applications. This tire is specially engineered with a block pattern that offers maximum stability and durability in the most difficult working conditions, also at high speeds.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 20"	94051243	6.50 - 20	5.50 F	4.00 E; 5.00 F	7.9	34.4	-	-	18	35	STD	10	TT	38 A8
	94038336	10.5 - 20	9	9 SDC	10.7	38.2	17.9	113.8	20	71	STD	10	TL	-
	94038404	12.5 - 20	11	12 SDC	13.2	41.3	18.9	123.2	23	105	STD	12	TL	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference