



## FL 639

### Description

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

### UM

US Standard

### Construction

 Radial

### Machinery

Agriculture ■ Spreader



Version

STANDARD

Tire Type

TL

Tyre size

800/40R22.5

LI/SS

168;D

## Dimensions US Standard

USA Code	94513420
SW (US) (in)	32.6
OD (US) (in)	47.7
SLR (US) (in)	21.2
RC (US) (in)	143.4
Rim Rec	AG 28.00
ECE	E11-106R-0010830

## Load Capacity (US)

mph / psi	12	17	23	29	35	41	46	52	58
45	3600	4620	5740	6530	7540	8550	9340	10240	11240
40	3960	5070	6300	7160	8280	9390	10250	11240	12350
30	4780	6130	7630	8670	10020	11360	12410	13600	14950
25	5290	6780	8430	9590	11080	12570	13720	15050	16530
20	5970	7650	9510	10820	12500	14170	15490	16970	18650
15	6250	8000	9950	11320	13070	14840	16200	17760	19510
5	7120	9120	11340	12900	14890	16900	18450	20230	22220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..