



## TR 391

### Description

TR 391 is an agro-industrial tire suitable for transport and compacting operations with sugar cane trailers and compactors. TR 391 features high load capacity and a longer service life.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ■ ,Industrial & Construction ■



Version	STANDARD
Tire Type	TL
Tyre size	14.9-24
LI/SS	124;A8

## Dimensions US Standard

USA Code	94033508
SW (US) (in)	15.9
OD (US) (in)	50.0
SLR (US) (in)	22.6
RC (US) (in)	149.8
Rim Rec	DW 13
Rim Alt	DW 11; DW 12; DW 13 L
TRA Code	R3

## Load Capacity (US)

mph / psi	26
25	3520

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..